

NSR®FPV TAS Anti-Drone

FPV anti-dron

To perform the functions of intercepting attack drones by detonating a combat fragmentation charge. It is effective for intercepting, including large UAVs. It can be used both independently and as part of a detection station. Optical target guidance and target capture allows to avoid enemy electronic warfare.

Charge initiation is possible remotely using a magnetometer, barometer, altimeter, accelerometer, lidar.

Frequency offset control and proprietary antennas for each frequency ranges:
190-1020 MHz, 2100 MHz-2700 MHz.



It can be used both independently and as part of a detection station.



Optical target guidance and target capture allows to avoid enemy electronic warfare.



Charge initiation is possible remotely using a magnetometer, barometer, altimeter, accelerometer, lidar.



Frequency offset control and proprietary antennas for each frequency ranges: 190-1020 MHz, 2100 MHz-2700 MHz.

This document is not contractual.
Subject to change without notice.

All rights reserved. © 2024 NSR



Contact
T. +971547670500
E: info@nsr-defense.ae
W: www.nsr-defense.ae

NSR®FPV TAS Anti-Drone

FPV anti-dron



MAIN SPECIFICATIONS

Size	7 inch
MTOW	1,5 kg
Engine type	electric
Maximum Range	17 km
Cruise Speed	300 km/h
Max flight time	20 min
Attack Guidance	GNSS, Visual Navigation optical guidance
Payload	1 kg

